

VOLKSWAGEN

Polo 1.4

1995 to 1997

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Polo 1.4

1995 to 1997

Type		AEX SOHC 8V 44kW
Capacity (cm ³) / number of cylinders		1390 / 4
Compression ratio / pressure	bar	10.2 / ≥7.0
Oil pressure	bar	[≥2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	84
Radiator cap pressure	bar	1.30 to 1.50

Fuel system

Polo 1.4

1995 to 1997

Idle speed - manual [auto]	rpm	770 to 970 [750 to 850] N/A
Fast idle speed - manual [auto]	rpm	2500 to 2800
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 [≤0.3]N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	–
O2 @ idle speed [3000 rpm] - see page VI	%	–
Carburettor / fuel injection		_Bosch
Type / ref		MP9.0-Motronic MPI
Main jet / needle		–
Injection pressure	bar	2.5
Pump pressure	bar	–
Octane rating	RON	95[U]

Ignition system

Polo 1.4

1995 to 1997

Type		Motronic
Ignition coil		–
Primary resistance	ohms	–
Ballast resistor	ohms	–
Voltage - Tmnl 15(+) to earth	V	–
Distributor		–
Points gap (air gap)	mm	–
Dwell angle	° (%)	–
Condenser capacity	µF	–
Rotation		–
Ignition timing - basic [static	° Crankshaft @ rpm	6±1 BTDC @ idle N/A
V = Vacuum NV = No Vacuum		–
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	–
	° Crankshaft @ rpm	–
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	–
	° Crankshaft @ rpm	–
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	–
Spark plugs		NGK/Bosch
Type		BUR6ET / W7LTCR
Electrode gap	mm	0.70 to 0.90 / 0.90 to 1.10

Electrical system

Polo 1.4

1995 to 1997

Battery	V / CC / RC	–
Alternator voltage / full load current / engine rpm		–
Starter motor current / voltage - cranking	A / V	–
- locked	A / V	–

Running gear

Polo 1.4

1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.5

Tyres		
Saloon	Size	155/70x13: 175/65x13
Estate / Van	Size	–
Pressure - front / rear - Saloon	bar	1.9 / 1.9
- Estate / Van	bar	–

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0°±10']
Camber		-0°25'±20'
Castor		1°20'±30'
King pin inclination		–

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0°20'±10']
Camber		-1°30'±10'

Torque wrench settings

Polo 1.4

1995 to 1997

Cylinder head - stage 1	Nm	40
- stage 2	Nm	60
Cylinder head - stage 3	Nm	+90°
- stage 4	Nm	+90°
Big-end bearings	Nm	30 +90° N
Main bearings	Nm	65 +90°
Clutch cover	Nm	20
Flywheel [driveplate]	Nm	60 +90° N
Front hubs	Nm	WSM
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	25

Capacities

Polo 1.4

1995 to 1997

Engine oil & filter	litres	3.4
Gearbox - 4-speed [5-speed]	litres	3.1
Automatic transmission - refill	litres	5.7 filled for life
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	45

Notes and Illustrations