

VOLKSWAGEN

Golf/Vento, 1.6i CAT

1993 to 1994

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Golf/Vento, 1.6i CAT

1993 to 1994

Type		ABU 55kW
Capacity (cm ³) / number of cylinders		1598 / 4
Compression ratio / pressure	bar	9.3 / ≥7.0
Oil pressure	bar	[2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	87 to 102
Radiator cap pressure	bar	1.3 to 1.5

Fuel system

Golf/Vento, 1.6i CAT

1993 to 1994

Idle speed - manual [auto]	rpm	750 to 850 N/A
Fast idle speed - manual [auto]	rpm	–
CO @ idle speed [3000 rpm] - see page VI	%	0.2 to 1.0 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	–
O2 @ idle speed [3000 rpm] - see page VI	%	–
Carburettor / fuel injection		Bosch
Type / ref		Mono-Motronic 1.2.3
Main jet / needle		–
Injection pressure	bar	0.8 to 1.2
Pump pressure	bar	–
Octane rating	RON	91[U]

Ignition system

Golf/Vento, 1.6i CAT

1993 to 1994

Type		DME Motronic
Ignition coil		Bosch N152
Primary resistance	ohms	0.5 to 1.2
Ballast resistor	ohms	–
Voltage - Tmnl 15(+) to earth	V	–
Distributor		Bosch
Points gap (air gap)	mm	–
Dwell angle	° (%)	–
Condenser capacity	µF	–
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	5±1 BTDC @ 750 to 850
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	34±3 BTDC @ ≥3000
	° Crankshaft @ rpm	–
	° Crankshaft @ rpm	–
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	–
	° Crankshaft @ rpm	–
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	–
Spark plugs		Bosch/Champion
Type		W8DTC / N9BYC
Electrode gap	mm	0.70 to 0.90

Electrical system

Golf/Vento, 1.6i CAT

1993 to 1994

Battery	V / CC / RC	12 / 220 / 44, 280 / 60Ah
Alternator voltage / full load current / engine rpm		–
Starter motor current / voltage - cranking	A / V	–
- locked	A / V	–

Running gear

Golf/Vento, 1.6i CAT

1993 to 1994

Brakes -		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	2.5

Tyres		
Saloon	Size	175/70x13:185/60x14:195/50x15
Estate / Van	Size	–
Pressure - front / rear - Saloon	bar	2.1 / 1.9 Vento: 2.0 / 1.8
- Estate / Van	bar	–

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0±10']
Camber		-30'±20'
Castor		+1°45'±30'
King pin inclination		–

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[+20'±10']
Camber		-1°30'±10' N/A

Torque wrench settings

Golf/Vento, 1.6i CAT

1993 to 1994

Cylinder head - stage 1	Nm	40
- stage 2	Nm	60
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	30 + 90°
Main bearings	Nm	65 ¹
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	60 + 90° N
Front hubs	Nm	265
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	25

Capacities


Golf/Vento, 1.6i CAT

1993 to 1994


Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	1.9
Automatic transmission - refill	litres	3.1
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	55

Notes and Illustrations

¹Replace with fully threaded shank bolts: 65 + 90°



1598 cm³



1598 cm³